

Tracking Mats



Heavy Duty Temporary Access Mat

The fast and safe way forward



Heavy Duty Temporary Access Mats

Unbreakable up to 80 tonnes*, EuroMat® is the ultimate, fast to install temporary access and ground protection mat for moving and operating plant, equipment and personnel over soft or sensitive ground.

Amazingly Tough & Flexible

Tough high density polyethylene (HDPE) EuroMat® are virtually indestructible, weigh only 35kg and the hand holds make moving and installation easy.

Anti Slip Surface

The engineered and unique chevron traction surface™ delivers ultimate grip and dispels mud and dirt whilst vehicles traverse over them. The chevron nub design also reduces sideways movement and slippage and delivers optimal forward traction.

Advantages

- Fast and easy to install
- Avoid property, heritage and environmental damage
- Avoid health and safety issues Reflective markings for night safety
- Unique chevron traction surface™
- Fast temporary access and working areas
- Low transport and handling costs
- Connection options for different terrain and equipment
- Designed and made in the UK

Semi-Permanent Specialist Applications

Connection options are available for more permanent situations, steep terrain and very heavy and tracked equipment.

*tested at National Physical Laboratory

Available Sizes

	Thickness	Dimension (w x l)	Weight per mat
Lift Track Mat	12mm	1200 x 2410mm	35kg
Lift Track Mat	12mm	600 x 2410mm	17kg

Material	Premium recycled or Virgin High Density Polyethylene (HDPE)
Colours Available	Black - recycled HDPE. Choice of colours - Virgin HDPE.
Connectivity	Standard connectors - 2 way and 4 way for longer term connection. Metal connectors for heavy and tracked equipment. 'Fast Fit' connectors for fast installation. Flex connectors for undulating ground. Metal U pins for slopes and cambers.

Optional extras	Non slip reflective markings and 'cats eyes' for night safety.
Environmental features	Weather proof, water and chemical resistant, usable in sub-zero temperatures. HD Polyethylene is resistant to acids, alkalis and solvents.
Customisation	Corporate logo and contact details can be added, subject to minimum order.
Guarantee	5 year warranty with a field life of 10 years when used as recommended.