

LIFT MRT A6

The MRTA6 attachment has a powerful 500kg lifting capacity, with 6 x 305mm suction pads. The MRT A6 also has a 'quadra tilt' system and variable configuration extension arm system which allow this mid-range attachment to work in many different scenarios.

500kg

KEY FEATURES

- Manual 360° continuous rotation, lockable at 8 intermediate positions
- Capacity 500kg
- Mechanically assisted tilting from vertical to horizontal
- 0° and 90° tilting locking latch system
- Multi-configurable with 4 extension arms
- Six 305mm diameter pads
- Two, independent vacuums circuits each with two vacuum reserve tank, gauge and non-return valve
- Maintenance-free vacuum pump
- Powered by 12v rechargeable battery with integral 110v or 240v charger and energy gauge
- Audio-visual low vacuum warning
- Not suitable for use in the rain – read more in our safety guide
- Maximum wind speed for safe use is 29km/h, 18mph, 16.5 knots or 8 m/s



SPECIFICATION

Dimensions	MAX: 1623mm x 2335mm x 290mm MIN: 829mm x 1188 x 290mm
Load Capacity: Per pad Maximum	500kg (6 pads) 336kg (4 pads) 168kg (2 pads)
Lifter Weight	86kg
Power Source	12V DC rechargeable battery
Battery Capacity	12v DC
Rotation Capability	360 degrees
Tilt Capability	+/- 90 DEGREES MANUAL
Low vacuum warning lights and buzzer	
Operating elevation	N/A
Operating Temperatures	0 – 100 degrees

DIMENSIONS (mm)

